

Safety Data Sheet
acc. to OSHA HCS

Printing date 04/12/2021

Reviewed on 04/12/2021

1 Identification

- **Product identifier**
- **Product name: Ethanol/Gasoline Kit 2 (high set): 70, 80, 90, 95, 100% (v/v) ethanol in gasoline**
- **Part number:** 403-1027
- **Application of the substance / the mixture** Reference material for laboratory use only
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
AMETEK Spectro Scientific Tel: +1 (978)486-0123
1 Executive Dr. Fax: +1 (978)486-0030
Chelmsford, MA 01824-2563
UNITED STATES OF AMERICA
- **Information department:** eMail: service.spectrosci@ametek.com
- **Emergency telephone number:**
Emergency Contact:
CHEMTREC
US & Canada- 800-424-9300;
International +1 703-741-5970
CHEMTREC A/C 619107

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 04/12/2021

Reviewed on 04/12/2021

Product name: Ethanol/Gasoline Kit 2 (high set): 70, 80, 90, 95, 100% (v/v) ethanol in gasoline

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Gasoil : fuels, diesel, nr 2

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** *Not applicable.*

· **vPvB:** *Not applicable.*

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/12/2021

Reviewed on 04/12/2021

Product name: Ethanol/Gasoline Kit 2 (high set): 70, 80, 90, 95, 100% (v/v) ethanol in gasoline

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description: Mixture: consisting of the following components.**

· **Dangerous components:**

| | | |
|-------------------------------------|---|--------|
| CAS: 64-17-5 RTECS: KQ6300000 | Ethanol Flam. Liq. 2, H225 | 50-95% |
| CAS: 68476-34-6 RTECS: LS9142500 | Gasoil : fuels, diesel, nr 2 Flam. Liq. 3, H226; Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Acute Tox. 4, H332; Skin Irrit. 2, H315 | 10-25% |

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:**
Rinse mouth. Do not induce vomiting.
Immediately call a doctor.
- **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed** No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:**
Mouth respiratory protective device.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/12/2021

Reviewed on 04/12/2021

Product name: Ethanol/Gasoline Kit 2 (high set): 70, 80, 90, 95, 100% (v/v) ethanol in gasoline

(Contd. of page 3)

Wear self-contained respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

| | | |
|--------------|---------|-----------|
| CAS: 64-17-5 | Ethanol | 1,800 ppm |
|--------------|---------|-----------|

· **PAC-2:**

| | | |
|--------------|---------|----------|
| CAS: 64-17-5 | Ethanol | 3300 ppm |
|--------------|---------|----------|

· **PAC-3:**

| | | |
|--------------|---------|-----------|
| CAS: 64-17-5 | Ethanol | 15000 ppm |
|--------------|---------|-----------|

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Store in cool, dry place in tightly closed receptacles.

Open and handle receptacle with care.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Please refer to the manufacturers certificate for specific storage and transport temperature conditions.

Store only in the original receptacle unless other advice is given on the CoA.

Keep container in a well-ventilated place. Keep away from sources of ignition and heat.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/12/2021

Reviewed on 04/12/2021

Product name: Ethanol/Gasoline Kit 2 (high set): 70, 80, 90, 95, 100% (v/v) ethanol in gasoline

(Contd. of page 4)

- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

CAS: 64-17-5 Ethanol

PEL Long-term value: 1900 mg/m³, 1000 ppm

REL Long-term value: 1900 mg/m³, 1000 ppm

TLV Short-term value: 1880 mg/m³, 1000 ppm

CAS: 68476-34-6 Gasoil : fuels, diesel, nr 2

TLV Long-term value: 100 mg/m³
as total hydrocarbons;Skin;inh. fraction + vapor

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

- **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The protective gloves to be used must comply with the specifications of EC Directive 89/686/EEC and the related standard EN374

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 04/12/2021

Reviewed on 04/12/2021

Product name: Ethanol/Gasoline Kit 2 (high set): 70, 80, 90, 95, 100% (v/v) ethanol in gasoline

(Contd. of page 5)



Protective gloves

· **Material of gloves**

Butyl rubber, BR
Nitrile rubber, NBR

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

| | |
|--------------------------|-----------------|
| · Form: | Liquid |
| · Color: | Light brown |
| · Odor: | Petrol-like |
| · Odor threshold: | Not determined. |

· **pH-value:** Not determined.

· **Change in condition**

| | |
|---------------------------------------|------------------|
| · Melting point/Melting range: | Not determined. |
| · Boiling point/Boiling range: | 78 °C (172.4 °F) |

· **Flash point:** 13 °C (55.4 °F)

· **Flammability (solid, gaseous):** Not determined.

· **Ignition temperature:** 220 °C (428 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

| | |
|-----------------|------------|
| · Lower: | 0.7 Vol % |
| · Upper: | 27.7 Vol % |

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/12/2021

Reviewed on 04/12/2021

Product name: Ethanol/Gasoline Kit 2 (high set): 70, 80, 90, 95, 100% (v/v) ethanol in gasoline

(Contd. of page 6)

| | |
|---|--|
| · Vapor pressure at 20 °C (68 °F): | 59 hPa (44.3 mm Hg) |
| · Density at 20 °C (68 °F): | 0.7915 g/cm ³ (6.60507 lbs/gal) |
| · Relative density | Not determined. |
| · Vapor density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| · Dynamic: | Not determined. |
| · Kinematic: | Not determined. |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity**
Stable under normal conditions.
No further relevant information available.
- **Chemical stability** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:**
Formation of toxic gases is possible during heating or in case of fire.
- **Possibility of hazardous reactions** May form flammable/explosive vapour-air mixture.
- **Conditions to avoid**
Sources of ignition
Heat.
- **Incompatible materials:** Strong oxidizing agents.
- **Hazardous decomposition products:** Formation of toxic gases is possible during heating or in case of fire.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Based on available data, the classification criteria are not met.
- **Sensitization:** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/12/2021

Reviewed on 04/12/2021

Product name: Ethanol/Gasoline Kit 2 (high set): 70, 80, 90, 95, 100% (v/v) ethanol in gasoline

(Contd. of page 7)

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

| | | |
|-----------------|------------------------------|----|
| CAS: 64-17-5 | Ethanol | I |
| CAS: 68476-34-6 | Gasoil : fuels, diesel, nr 2 | 2B |

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Dispose in accordance with national regulations.

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS



Printing date 04/12/2021

Reviewed on 04/12/2021

Product name: Ethanol/Gasoline Kit 2 (high set): 70, 80, 90, 95, 100% (v/v) ethanol in gasoline

(Contd. of page 8)

14 Transport information

| | |
|---|---|
| · UN-Number | UN1993 |
| · DOT, ADR, IMDG, IATA | Flammable liquids, n.o.s. (Ethanol, Diesel fuel) |
| · DOT | 1993 Flammable liquids, n.o.s. (Ethanol, Diesel fuel) |
| · ADR | FLAMMABLE LIQUID, N.O.S. (ETHANOL (ETHYL ALCOHOL), DIESEL FUEL) |
| · IMDG | FLAMMABLE LIQUID, N.O.S. (ETHANOL, DIESEL FUEL) |
| · IATA | FLAMMABLE LIQUID, N.O.S. (ETHANOL, DIESEL FUEL) |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · ADR, IMDG, IATA | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · Packing group | II |
| · DOT, ADR, IMDG, IATA | II |
| · Environmental hazards: | Not applicable. |
| · Special precautions for user | Warning: Flammable liquids |
| · Hazard identification number (Kemler code): | 33 |
| · EMS Number: | F-E,S-E |
| · Stowage Category | B |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADR | |
| · Excepted quantities (EQ) | Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 04/12/2021

Reviewed on 04/12/2021

Product name: Ethanol/Gasoline Kit 2 (high set): 70, 80, 90, 95, 100% (v/v) ethanol in gasoline

(Contd. of page 9)

· **UN "Model Regulation":** UN 1993 FLAMMABLE LIQUIDS, N.O.S. (ETHANOL, DIESEL FUEL), 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

CAS: 64-17-5 Ethanol

CAS: 68476-34-6 Gasoil : fuels, diesel, nr 2

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value)**

CAS: 68476-34-6 Gasoil : fuels, diesel, nr 2

A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **Hazard pictograms**



GHS02

GHS07

GHS08

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/12/2021

Reviewed on 04/12/2021

Product name: Ethanol/Gasoline Kit 2 (high set): 70, 80, 90, 95, 100% (v/v) ethanol in gasoline

(Contd. of page 10)

- **Signal word** *Danger*
- **Hazard-determining components of labeling:**
Gasoil : fuels, diesel, nr 2
- **Hazard statements**
H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 If swallowed: Immediately call a poison center/doctor.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

The information in this Safety Data Sheet meets the requirements of the United States OCCUPATIONAL SAFETY AND HEALTH ACT and regulations promulgated thereunder (29 CFR 1910.1200 et. seq.) This document is intended only as a guide to the appropriate precautionary handling of the material by a person trained in, or supervised by a person trained in, chemical handling. The user is responsible for determining the application. Depending on usage, protective clothing including eye and face guards and respirators must be used to avoid contact with material or breathing chemical vapors/fumes. Exposure to this product may have serious adverse health effects. This chemical may interact with other substances. Since the potential uses are so varied, we cannot warn of all of the potential dangers of use or interaction with other chemicals or materials. We warrant that the chemical meets the specifications set forth on the label. We (AMETEK - Spectro Scientific) disclaim any other warranties, expressed or implied with regard to the product supplied hereunder, its merchantability or its fitness for a particular purpose. The user should recognize that this product can cause severe injury and even death, especially if improperly handled or the known dangers of use are not heeded. Read all precautionary information.

- **Contact:**
- **Date of preparation / last revision** 04/12/2021 / -
- **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/12/2021

Reviewed on 04/12/2021

Product name: Ethanol/Gasoline Kit 2 (high set): 70, 80, 90, 95, 100% (v/v) ethanol in gasoline

(Contd. of page 11)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Carc. 2: Carcinogenicity – Category 2

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

• **Sources**

Tables 3.1 and 3.2 from Annex 6 of EC 1272/2008, EC 1907/2006, EH40/2005 as amended 2011, Registry of Toxic Effects of Chemical Substances (RTECS), The Dictionary of Substances and their Effects, 1st Edition, IUCLID.

• **Data compared to the previous version altered.** All sections have been updated.