

# SAFETY DATA SHEET

## 1. Identification

<b>Product identifier</b>	<b>LNF-545 Ferrous Calibration Fluid for Magnetometer</b>	
<b>Other means of identification</b>		
<b>Product code</b>	LNF-545	
<b>Recommended use</b>	Reference material for laboratory use only.	
<b>Recommended restrictions</b>	None known.	
<b>Manufacturer/Importer/Supplier/Distributor information</b>		
<b>Company name</b>	AMETEK - Spectro Scientific	
<b>Address</b>	1 Executive Drive Chelmsford , MA 01824 United States	
<b>E-mail</b>	service.spectrosci@ametek.com	
<b>Website</b>	www.spectrosci.com	
<b>Telephone</b>	+1 (978) 486-0123	
<b>Emergency telephone</b>	CHEMTREC US & Canada 800-424-9300 International +1 703-741-5970 CHEMTREC A/C 619107	

## 2. Hazard(s) identification

<b>Physical hazards</b>	Not classified.	
<b>Health hazards</b>	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 3
	Hazardous to the aquatic environment, long-term hazard	Category 3
<b>OSHA defined hazards</b>	Not classified.	

### Label elements



<b>Signal word</b>	Danger	
<b>Hazard statement</b>	May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.	
<b>Precautionary statement</b>		
<b>Prevention</b>	Avoid release to the environment.	
<b>Response</b>	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.	
<b>Storage</b>	Store locked up.	
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.	
<b>Hazard(s) not otherwise classified (HNOC)</b>	Repeated exposure may cause skin dryness or cracking.	
<b>Supplemental information</b>	None.	

## 3. Composition/information on ingredients

### Mixtures

Chemical name	CAS number	%
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	70 - 80
Distillates (petroleum), hydrotreated middle	64742-46-7	25 - 35
Distillates (petroleum), hydrotreated light	64742-47-8	15 - 25
Butylated hydroxytoluene	128-37-0	0.25 - 1
Phenol, isobutylated, phosphate (3:1)	68937-40-6	0.25 - 1

**Composition comments** The specific chemical identity and/or exact percentage of component(s) have been withheld as a trade secret. All concentrations are in percent by weight. Components not listed are either non-hazardous or are below reportable limits.

#### 4. First-aid measures

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

**Skin contact** Wash off with soap and water. Get medical attention if irritation develops and persists.

**Eye contact** Rinse with water. Get medical attention if irritation develops and persists.

**Ingestion** Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

**Most important symptoms/effects, acute and delayed** Swallowing of the liquid, or vomiting as a result, may result in aspiration into the lungs. Aspiration may cause pulmonary edema and pneumonitis. Be aware that symptoms of lung edema (shortness of breath) may develop up to 24 hours after exposure. Repeated exposure may cause skin dryness or cracking.

**Indication of immediate medical attention and special treatment needed** Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

#### 5. Fire-fighting measures

**Suitable extinguishing media** Foam. Dry chemicals. Carbon dioxide (CO<sub>2</sub>). Sand. Earth.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical** During fire, gases hazardous to health may be formed.

**Special protective equipment and precautions for firefighters** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**Fire fighting equipment/instructions** Cool containers exposed to heat with water spray and remove container, if no risk is involved.

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials.

**General fire hazards** Will burn if involved in a fire.

#### 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**Methods and materials for containment and cleaning up** Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Clean contaminated area with oil-removing material.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

**Environmental precautions** Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

### Precautions for safe handling

Avoid prolonged or repeated contact with skin. Do not taste or swallow. Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored, and processed. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

### Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat and sources of ignition. Store in cool, dry, well ventilated area. Store in original tightly closed container. Protect from direct sunlight or ultraviolet light. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	PEL	5 mg/m <sup>3</sup>	Mist.
		2000 mg/m <sup>3</sup>	
		500 ppm	
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	PEL	5 mg/m <sup>3</sup>	Mist.

#### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Butylated hydroxytoluene (CAS 128-37-0)	TWA	2 mg/m <sup>3</sup>	Inhalable fraction and vapor.
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction.
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction.

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Butylated hydroxytoluene (CAS 128-37-0)	TWA	10 mg/m <sup>3</sup>	
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	100 mg/m <sup>3</sup>	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Ceiling	1800 mg/m <sup>3</sup>	
	STEL	10 mg/m <sup>3</sup>	Mist.
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	STEL	10 mg/m <sup>3</sup>	Mist.
	TWA	5 mg/m <sup>3</sup>	Mist.

### Biological limit values

No biological exposure limits noted for the ingredient(s).

### Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles). Face shield is recommended.

<b>Skin protection</b>	
<b>Hand protection</b>	Wear appropriate chemical resistant gloves. Full contact: Glove material: PVC, neoprene, nitrile rubber; Layer thickness: > 0.35 mm; Breakthrough time: 240 min. Splash contact: Glove material: Nitrile; Layer thickness: > 0.35 mm; Breakthrough time: 240 min. Other suitable gloves can be recommended by the glove supplier.
<b>Skin protection</b>	
<b>Other</b>	Wear suitable protective clothing. Chemical/oil resistant clothing is recommended.
<b>Respiratory protection</b>	If mist is generated (heating, spraying) and engineering controls are not sufficient, wear approved organic vapor respirator suitable for oil mist. Wear NIOSH approved respirator appropriate for airborne exposure at the point of use. Check with respiratory protective equipment suppliers.
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>General hygiene considerations</b>	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

### Appearance

<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	Red.
<b>Odor</b>	Petroleum-like.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not applicable.
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	> 536 °F (> 280 °C)
<b>Flash point</b>	>=105.0 °C (>= 221.0 °F) Pensky-Martens Closed Cup
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Will burn if involved in a fire.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	1 % v/v
<b>Flammability limit - upper (%)</b>	10 % v/v
<b>Vapor pressure</b>	< 0.5 Pa (20°C / 68°F) estimated
<b>Vapor density</b>	> 1 estimated
<b>Relative density</b>	0.87
<b>Relative density temperature</b>	59 °F (15 °C)
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Negligible.
<b>Partition coefficient (n-octanol/water)</b>	> 6
<b>Auto-ignition temperature</b>	> 608 °F (> 320 °C)
<b>Decomposition temperature</b>	Not available.
<b>Other information</b>	
<b>Density</b>	870.00 kg/m <sup>3</sup>
<b>Explosive properties</b>	Not explosive.
<b>Kinematic viscosity</b>	14.1 mm <sup>2</sup> /s ASTM D445
<b>Kinematic viscosity temperature</b>	104 °F (40 °C)
<b>Oxidizing properties</b>	Not oxidizing.
<b>Pour point</b>	≤ -60 °C (< -76 °F) ASTM D 97

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Keep away from heat, sparks and open flame or any other ignition source. Protect from direct sunlight or ultraviolet light. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors. Soot.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Inhalation of oil mist or vapors formed during heating of the product will irritate the respiratory system and provoke coughing.
<b>Skin contact</b>	Repeated exposure may cause skin dryness or cracking.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

**Symptoms related to the physical, chemical and toxicological characteristics** Swallowing or vomiting of the liquid may result in aspiration into the lungs. Aspiration may cause pulmonary edema and pneumonitis. Be aware that symptoms of lung edema (shortness of breath) may develop up to 24 hours after exposure. Repeated exposure may cause skin dryness or cracking.

### Information on toxicological effects

**Acute toxicity** Not expected to be acutely toxic.

Components	Species	Test Results
------------	---------	--------------

Butylated hydroxytoluene (CAS 128-37-0)

#### Acute

##### **Dermal**

LD50	Rat	> 2000 mg/kg
------	-----	--------------

##### **Oral**

LD50	Rat	> 2930 mg/kg
------	-----	--------------

**Skin corrosion/irritation** Repeated exposure may cause skin dryness or cracking.

**Serious eye damage/eye irritation** Direct contact with eyes may cause temporary irritation.

### Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** Not classified.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** Not classifiable as to carcinogenicity to humans.

#### **IARC Monographs. Overall Evaluation of Carcinogenicity**

Butylated hydroxytoluene (CAS 128-37-0)	3 Not classifiable as to carcinogenicity to humans.
---	---

Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	3 Not classifiable as to carcinogenicity to humans.
---	---

#### **NTP Report on Carcinogens**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Known To Be Human Carcinogen.
---	-------------------------------

#### **OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)**

Not listed.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.

**Specific target organ toxicity - single exposure** Not classified.

<b>Specific target organ toxicity - repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.
<b>Chronic effects</b>	Prolonged inhalation may be harmful.
<b>Further information</b>	Symptoms may be delayed.

## 12. Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Components	Species	Test Results
Butylated hydroxytoluene (CAS 128-37-0)		
<b>Aquatic</b>		
<i>Chronic</i>		
Crustacea	NOEC Daphnia magna	0.07 mg/l, 21 days
<b>Persistence and degradability</b>	No data available.	
<b>Bioaccumulative potential</b>	No data available on bioaccumulation.	
<b>Partition coefficient n-octanol / water (log Kow)</b>		
LNF-545 Ferrous Calibration Fluid for Magnetometer	> 6	
<b>Mobility in soil</b>	The product is insoluble in water.	
<b>Other adverse effects</b>	Oil spills are generally hazardous to the environment.	

## 13. Disposal considerations

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport information

### DOT

Not regulated as dangerous goods.

### IATA

Not regulated as dangerous goods.

### IMDG

Not regulated as dangerous goods.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.

## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

### CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

### SARA 304 Emergency release notification

Not regulated.

## OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

### Toxic Substances Control Act (TSCA)

All components of the mixture on the TSCA 8(b) inventory are designated "active".

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SARA 302 Extremely hazardous substance

Not listed.

**SARA 311/312 Hazardous chemical** Yes

**Classified hazard categories** Aspiration hazard

#### SARA 313 (TRI reporting)

Not regulated.

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

### US state regulations

#### US. Massachusetts RTK - Substance List

Butylated hydroxytoluene (CAS 128-37-0)  
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)  
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)  
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)

#### US. New Jersey Worker and Community Right-to-Know Act

Butylated hydroxytoluene (CAS 128-37-0)  
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

#### US. Pennsylvania Worker and Community Right-to-Know Law

Butylated hydroxytoluene (CAS 128-37-0)  
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)  
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)

#### US. Rhode Island RTK

Butylated hydroxytoluene (CAS 128-37-0)  
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)  
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)  
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)

### California Proposition 65



**WARNING:** This product can expose you to chemicals including Nickel, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### California Proposition 65 - CRT: Listed date/Carcinogenic substance

Cobalt (CAS 7440-48-4) Listed: July 1, 1992  
Nickel (CAS 7440-02-0) Listed: October 1, 1989

#### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)  
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)  
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)  
Phenol, isobutylated, phosphate (3:1) (CAS 68937-40-6)

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

**Issue date** 26-March-2021

**Revision date** -

**Version #** 01

**NFPA ratings**



**Disclaimer**

AMETEK - Spectro Scientific cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.